






PureChill-900









Standard Features

PureChill™ Technology





- Low Height (only 16 1/2") fits under standard cabinets
- · Integrated Filter Monitor ensures freshly filtered water
- ProTekk™ Auto Safety-Shut-Off Valve provides peace of mind
- Two temperature system
 Cold: 37-50° F, Adjustable Hot: 180° F, Autocontrol
 LED indicator for Hot and Cold water on the front panel
- Tall fill opening allows larger cups, mugs or reusable bottles
- Hygienic dispensing touch pad control with no-touch dispensing faucet
- · Easy to clean control panel
- Individual on/off control switches for cold and hot water on rear panel
- Built-in Standard Dual-Cartridge filtration system is easily accessed for replacement
- Attractive LED lighted dispense area
- Award winning design
- 1 year limited warranty
- 3 year compressor warranty



Dimensions (inches)

Specifications

Shipping Weight: 50 lb.
Dimension: 13"W x 16"D x 16.5"H
Cooling Rate: 2.8 gal/hr 37-50 °F
Hot tank volume .5 gal
Heating Rate: 1.3 gal/hr 180 °F
Voltage: 115 VAC

Power Required: 600w max

Filter System

Standard Filter *900F*Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Automatic tank full control

Fully assembled

ADA compliant

ORDERING

2-Temp Model - Standard Filtration PWC-900F
2-Temp Model PWC-900
Replacement Filters Sediment TF-4113
Carbon TF-4115



