


PureWaterCooler™

by VERTEX

PureChill-9501




Cleaner. Safer. Better.

This new Vertex 3-temp cooler offers cold, hot and room water along with the new, more reliable capacitive touch dispensing.

The newest VERTEX **PureWaterCooler** Cold, Hot and Room temperature water dispenser uses **PureChill™** Technology to eliminate the need for an open reservoir to store water. The closed system keeps environmental contaminants out. The reliable capacitive touch control panel dispenses water safely to your cup.



PureChill-9501



PureChill Cooling Technology




Optional Integrated Filter Monitor



ProTekk Auto-Safety Shut-off valve

Standard Features

- PureChill™ Technology
- Closed system keeps environmental contaminants out
- Capacitive touch dispense button for ease and durability
- ProTekk™ Auto Safety-Shut-Off Valve provides peace of mind
- Cold: 37-50° F, Adjustable • Hot: 180° F, Autocontrol
- LED indicator for Hot and Cold water on the front panel
- Tall fill opening allows larger cups, mugs or reusable bottles
- Easy to clean control panel
- Individual on/off control switches for cold and hot water on rear panel
- Built-in filtration system is easily accessed for replacement
- Available with RO system or Standard Dual-Cartridge filtration system
- RO system comes with 2.5 gallon pressurized water storage tank
- Filter assembly is front door accessible
- Optional Integrated Filter Monitor available
- Attractive LED lighted dispense area
- Award winning design
- 1 year limited warranty
- 3 year compressor warranty



Specifications

Shipping Weight: 81 lb.
 Dimension: 13"W x 16"D x 51.5"H
 Cooling Rate: 2.8 gal/hr 37-50 °F
 Hot tank volume .5 gal
 Heating Rate: 1.3 gal/hr 180 °F
 Voltage: 115 VAC
 Power Required: 600w max



Filter System

Standard Filter **9501F**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon
 Reverse Osmosis Filter **9501R**
 Above 2 stages plus
Stage 3: 100-GPD RO Membrane
 Automatic tank full control
 Partial assembly required

ORDERING

3-Temp Model with 100 GPD RO Filtration	PWC-9501R*
3-Temp Model with Standard Filtration	PWC-9501F
3-Temp Model	PWC-9501
Replacement Filters	Sediment TF-4113
	Carbon TF-4115
	RO membrane, 100 GPD MA-4205

*Includes 2.5 gallon bladder tank for pressurized water storage

Authorized Dealer