

PureWaterMachine™

by VERTEX®

5-Stage RO w/Booster Pump

Booster pump provides needed pressure.

Standard Features

- Auto shut-off valve (conserves water)
- Flow restrictor – modified capillary
- Long reach, non-airgap faucet
- Feed water connector – threaded inlet adapter with metal ballvalve
- Drain clamp
- 1/4 inch flexible polyethylene tubing w/JACO compression fittings
- 2 year limited warranty

This 5-stage **Vertex PureWaterMachine** is designed to ensure premium water quality even when the water pressure is below 40-psi - common in well water systems. The booster pump provides a pressure of 80psi to the RO membrane to operate the system at peak efficiency. The additional Carbon Block filter is added to treat water containing high VOC's, high levels of chlorine, or where odor or taste is a problem. Two sediment filters and one carbon filter can be used where there is heavy sediment load. The system comes complete ready to install with connection hardware, tubing, faucet and instruction manual.

Specifications: Shipping Weight: 28 lb. Dimension: 15.5"L x 7"W x 18"H. Tank: 12 dia. x 15.5"H
Conditions of Use: Water must be microbiologically safe; System pressure, 40 min to 100 max psi; Temperature, 40 to 100° F; PH Range, 3 to 10; Turbidity – less than 1.0 NTU; TDS, 1500 PPM max

ORDERING

4 stage Reverse Osmosis	PT-4.0/5/P
Air Gap Faucet option	add /AG
3/8" Line to Faucet option	add /3/8
Self-piercing Saddle Valve option	add /SV
Quick Connect Fittings option	add /QC
Filter Replacement Kit	FK-101



IAPMO R&T
WATER QUALITY
 PLATINUM SEAL
 IAPMO RESEARCH AND TESTING

**CERTIFIED
 REDUCED
 CONTAMINANTS**

Arsenic
 Barium
 Cadmium
 Chromium III & VI
 Copper
 Fluoride
 Lead
 Radium 226 & 228
 Selenium
 Turbidity
 TDS

Tested for structural integrity, chemical extraction and reduction of contaminants

STAGE ONE

Sediment Filter, 5-Micron Polyspun Cartridge
 2 1/2" dia. x 9 3/4" long

STAGE TWO

Activated Carbon Block Filter
 5 Micron, 2 1/2" dia. x 9 3/4" long

STAGE THREE

Activated Carbon Block Filter
 5 Micron, 2 1/2" dia. x 9 3/4" long

STAGE FOUR

Reverse Osmosis Membrane, Filmtec
 36 GPD TFC @ 65 PSI Pressure Differential

STAGE FIVE

Post-Filter, In-Line, Granular Activated Carbon
 2" dia. x 10" long

BOOSTER PUMP

Flow through diaphragm pump, 24 volt DC
 115 VAC/24 VDC 60 Hz. Boosts system pressure to 80 PSI

TANK

4.0 Gallon Metal Tank (metal tank available),
 Pre-pressurized with Butyl Bladder (2.5 gal. water capacity when full)

Authorized Dealer